

# CASIO®

## XJ-V1 CORE SERIES



## XJ-V1 CORE SERIES



The XJ-V1 incorporates essential features with Casio's Industry Leading LampFree® Technology to create a budget friendly projector. It delivers reliable long term operation, exceptional image quality, 2700 lumens of brightness, and connectivity ideal for use in classrooms, on the road or in the boardroom. The XJ-V1 uses LampFree technology which makes it environmentally friendly and very cost effective to operate.

### KEY FEATURES

- Compact Design
- Premium Quality, Made in Japan
- Dust resistant construction
- 5 Year Warranty on Light Source
- 3 Year Warranty on Labour & Service
- 2700 Lumens
- 1.1X Optical Zoom
- Input/Output: RGB, HDMI, RS-232C
- DLP technology
- XGA (1024 x 768) resolution
- Multiple mounting options for easy swap out

### LAMPFREE BENEFITS

- 20 000 hour operating life
- No lamp replacement
- Quick start (5 seconds to full brightness)
- Instant off – no cool down period
- Low energy power consumption
- Low maintenance - zero downtime
- Laser & LED Hybrid Lightsource
- Mercury Free



## XJ-V1 SPECIFICATIONS

SPECIFICATIONS	SLIM
Native Resolution	XGA (1024 x 768) 786,432 pixels
Native Aspect Ratio	4:03
Brightness	2700 Lumens
Display Device	0.55" DLP® chip
Contrast Ratio	20000:1
Lens Type	1.1X Manual Zoom & Focus
Lens Offset	72%
Light Source	Casio Laser & LED Hybrid
Estimated Light Source Life	Up to 20,000 Hours
PROJECTION RANGE	
60-inch screen	5.9-6.5 ft

SPECIFICATIONS	SLIM
100-inch screen	10.1-11.2 ft
Minimum	2.7 ft @ 30inch
Throw Ratio	1.54-1.71:1 @ 60inch
Keystone Correction	Vertical + or - 30° (Manual)
Color Reproduction	Full color (up to 1.07 billion colors)
Power Source	AC 100 ~240V, 50/60 Hz
POWER CONSUMPTION	
Operating	Approx. 155W Eco OFF, Bright Mode ON
Standby *100 to 120V	0.15 w
VIDEO SIGNAL COMPATABILITY	
Video Systems	NTSC/ PAL/ PAL-N/ PAL-M/ PAL60/ SECAM
DTV/HDTV	480i/480P/576i/576P/720P/1080i/1080p
Maximum Computer Input	UXGA (1600 x 1200)
INPUTS	
RGB/Component Video Input	mini D-Sub 15 pin x 1 Also use as YCbCr/YPbPr input - commercially available adapter required
HDMI	HDMI Type A x 1 (480p~1080p) HDCP and audio support
Composite Video	No
Audio	3.5mm Stereo
USB	No
USB Display	No
Logo Transfer	No
Built-in Memory	No
Wireless Capability (USB Only)	No
OUTPUTS	
Audio	3.5 mm Mini - Stereo Variable Audio
AUDIO AND CONTROL SYSTEMS	
Audio system	No
Control Terminal	RS-232 (Dsub 9 Pin) x 1
LAN	No
USAGE ENVIRONMENT	
Operating Temperature	41~95°F
Operating Humidity	20~80% (non condensation)
High Altitude Mode	Yes (for operation 5,000~10,000 ft)
Extended operation (24 x 7)	Yes Note: Projector must be turned off once every 24 hours
Rotation Projection	No
Closed Captioning	No
Remote Control Range	N/A
SECURITY COMPATIBILITY	
Kensington Compatible	Yes
Power On Password	Yes
Ceiling Mountable	Yes, available and sold separately by 3rd party vendors
Ceiling Mount Screws	M4 x 4 ( not included)
(Type x Length) (Qty)	Insert depth (5-8 mm)
Limited Warranty	3 Years Parts & Labor plus 5 years or 10,000 hours on light source, see Warranty Statement included with product for complete details
Included Accessories	Remote Control, Power Cord, RGB Cable, Warranty, Setup Guide
Cabinet Color	White
DIMENSION (W X D X H)	
Including Projections	10.6" x 10.6" x 3.5"
Packing Information	8.6 lbs
UPC Code	'079767483470
Manufactured in	Japan